FACE, HEAD, & NECK PROTECTION



AS1200 PROTECTIVE FACESHIELD - HRC 2



12 CAL/CM²

NEW REVOLUTIONARY AS1200HAT

Salisbury by Honeywell's NEW revolutionary AS1200HAT is a Weight Balancing Arc Flash Protection Face Shield, that stows in a balanced, compact position, centered over the top of the hard hat when not needed. The AS1200HAT has an ATPV rating of 12cal/cm² and utilizes nanotechnology to provide a more transparent window for improved visibility. The shield/window is designed to be easily replaced without tools. The faceshield unit includes ventilation ribs that allow a natural convection air flow through the top of the face shield. This reduces fogging of the visor, lowers CO2 levels and improves comfort for the user.

AS1200 SERIES

7.5" x 20" viewing area Extra light tint .06" thick Absorbs >99.9% of harmful UV radiation Resistant to fogging Meets current ANSI Z87.1, CSA, and tested to ASTM F2178 specifications **OPTIONAL ACCESSORIES**

AFLENS ANTI-FOG INNER LENS

- Includes an air spaced design that decreases fogging
- Natural convection air flow design helps minimizes fogging
- Shield meets the ASTM requirements for an Anti-Fog Lens

ASFL FLAME RESISTANT ATTACHABLE TASK LIGHTS

The arc tested ASFL FR task light features a high intensity long lasting white LED lamp with an overall brightness of 7 lumens. From a 24 inch distance, the beam is approximately 6-7 inch in diameter. The high intensity illumination is very useful when working up close. 2 AAA batteries provide 14-15 hours of high brightness. NOTE: The AS1200HAT can hold 2 ASFL task lights. The FLKIT only contains 1 task light and 1 clip.

AS12CLR TRANSPARENT CHIN GUARD

The AS12CLR Transparent Chin Guard dramatically increases the user's peripheral view. The enhanced viewing area increases worker performance and productivity. The highly transparent chin guard allows improved awareness and greater safety.

| Cat. No. | Description |
|--------------|--|
| AS1200HAT | $\operatorname{\sf NEW}$ weight balancing arc flash protection faceshield unit w/ hard hat |
| AS1200HATCLR | NEW AS1200HAT w/ transparent chin guard |
| AS1200 | NEW weight balancing arc flash protection faceshield unit. |
| AFLENS | NEW Anti-Fog Inner Lens |
| ASFL | NEW FR Attachable Task Lights (1) |
| AS12CLIP | NEW Replacement Clips Set (2) for AS1200HAT Shield |
| FLCLIP | NEW Attachable Task Light Clip (1) |
| FLKIT | NEW Attachable Task Light (1) & FLCLIP |
| AS12CLR | NEW Transparent Chin Guard |
| | |





SALISBURY ADVANTAGE



If You Need it, Request it. Call customer service if you need something not seen here.

9

AS1200FB FULL BRIM PROTECTIVE FACESHIELD - HRC 2

12 CAL/CM^2







NEW FULL BRIM AS1200FB

Salisbury by Honeywell's NEW revolutionary AS1200FB is a weight balancing arc flash protection faceshield that fits ALL full brim hard hats regardless of the manufacturer. The shield easily stows in a balanced, compact position, centered over the top of the full brim hard hat when not needed.

The AS1200FB assembly attaches to the full brim hard hat with an elastomeric band that secures the bracket onto the brim. All parts are dielectric and specifically designed for arc flash protection.

The AS1200FB has an ATPV rating of 12cal/cm² (NFPA 70E HRC 2) and utilizes nanotechnology and an anti-fog coating, to provide a clearer, more transparent window for improved visibility. The faceshield unit includes an upper bracket ventilation feature that allows a natural air flow through the top of the face shield. This reduces fogging of the visor, lowers CO2 levels and improves comfort for the user.

OPTIONAL ACCESSORIES

ASFL FLAME RESISTANT ATTACHABLE TASK LIGHTS

The arc tested ASFL FR task light features a high intensity long lasting white LED lamp with an overall brightness of 7 lumens. From a 24 inch distance, the beam is approximately 6-7 inch in diameter. The high intensity illumination is very useful when working up close. 2 AAA batteries provide 14-15 hours of high brightness. NOTE: The AS1200HAT can hold 2 ASFL task lights. The FLKIT only contains 1 task light and 1 clip.

TRANSPARENT CHIN GUARD

The Transparent Chin Guard dramatically increases the user's peripheral view. The enhanced viewing area increases worker performance and productivity. The highly transparent chin guard allows improved awareness and greater safety.

NEW REVOLUTIONARY AS1200FB

7.5" x 20" viewing area Extra light tint .06" thick Absorbs >99.9% of harmful UV radiation Resistant to fogging Meets current ANSI Z87.1 and tested to ASTM F2178 specifications

Unique Weight Balancing Design Optional Task Light Feature Replaceable Window, NO TOOLS REQUIRED. Fits ALL Full Brim Hard Hats Ventilated Design Adjustable Pivot Tension Can Be Easily Removed from the Hard Hat One Hand Operation

| Cat. No. | Description |
|-------------|--|
| AS1200FB | NEW 12 cal/cm², Arc Flash Protection Faceshield Unit for Full Brim Hard Hats |
| AS12ORG-FB | NEW Orange Chin Guard for AS1200FB |
| AS12CLR-FB | NEW Transparent Chin Guard for AS1200FB |
| AS1200FS-FB | NEW Replacement Faceshield/Window 12 cal/cm² for AS1200FB Full Brim |
| ASFL | NEW FR Attachable Task Lights (1) |
| FLCLIP | NEW Attachable Task Light Clip (1) |
| FLKIT | NEW Attachable Task Light (1) & FLCLIP |

AS1000/AS1500 SERIES PROTECTIVE FACESHIELD UNITS & ACCESSORIES - HRC 2

 10 CAL/CM^2



AS1000 SERIES

10 cal/cm² ATPV rating when used with the included chin cup

7.5" x 20" viewing area

Extra light tint

.06" thick


Absorbs >99.9% of harmful UV radiation

Resistant to fogging

Meets current ANSI Z87.1 and tested to ASTM F2178 specifications

| Cat. No. | Description | | | | | |
|-----------|--|--|--|--|--|--|
| AS1000 | AS1000FS shield w/ ASCP chin cup & slotted ASSLB bracket. Fits most slotted front brim hard hats. | | | | | |
| AS1000U | AS1000FS shield w/ ASCP chin cup & universal BRACKET. Fits most front brim hard hats. | | | | | |
| AS1000FB | AS1000FS shield w/ ASCP chin cup & universal FBBRACKET. Fits most full brim hard hats. | | | | | |
| AS1000R | AS1000FSR shield w/ ASCP chin cup and ASRHG4 pin lock head band w/ 4" arc guard. | | | | | |
| AS1000HAT | AS1000 w/ SA79R front brim hard hat. | | | | | |
| ASBAG | Cotton canvas storage bag w/ drawstring closure & fleece interior, for AS1000 series products. | | | | | |
| SA79* | Peak front brim hard hat with rain trough, 4-point nylon suspension, pin-lock adjustment. ANSI & CSA Type I, Class E. Dielectrically rated. ANSI Z89.1-2003 | | | | | |
| SA79R* | Peak front brim hard hat with rain trough, 4-point nylon suspension, ratcheting adjustment. ANSI & CSA Type I, Class E. Dielectrically rated. ANSI Z89.1-2003 | | | | | |






| *IMPORTANT - Please add the color code to the end of hard hat # | | | | | |
|--|--------|--|--|--|--|
| (EX:SA7901 - White ANSI Type I, dielectric front brim hard hat w/quick-fit 4-point suspension) | | | | | |
| Color Codes Stock Colors | | | | | |
| 01 | White | | | | |
| 02 03 | Yellow | | | | |
| 03 | Orange | | | | |

If You Need it, Request it. Call customer service if you need something not seen here.

REPLACEMENT ARC FLASH PROTECTION LENSES

8 - 100 CAL/CM 2



AS1000/AS1200/AS1500 & PRO-HOOD®

8 cal/cm² to 100 cal/cm² ATPV ratings

7.5" x 20" viewing area for replacement AS1000 Protective Shield lenses 10" x 20" viewing area for replacement PRO-HOOD® lenses 4000V and 10000V lenses have two layers of protection Extra light tint .06" thick Absorbs >99.9% of harmful UV radiation

Resistant to fogging

Meets current ANSI Z87.1 and tested to ASTM F2178 specifications **NEW** AFLENSU - The universal inner lens is a field installed anti-fog lens for PRO-HOOD arc flash protective switching hoods. Installs quickly without tools to the inside of the PRO-HOOD faceshield and can be removed for cleaning or replacement.

| Cat. No. | Description | | | | | |
|-----------|---|--|--|--|--|--|
| AS1000FS | Replacement face shield for AS1000HAT, AS1000FB, and AS1000U. Used with the ASSLB, FBBRACKET, or BRACKET brackets and ASCP. | | | | | |
| AS1200FS | NEW Replacement window for AS1200HAT, 12cal/cm². | | | | | |
| AS1000FSR | Replacement face shield for AS1000R. Used with the ASRHG4 bracket and ASCP. | | | | | |
| AFLENSU | NEW Inner Anti-Fog Lens for PRO-HOOD®. | | | | | |
| 1000V | Replacement lens, with hook & pile attachment, for NEW DESIGN 8cal/cm ² to 20cal/cm ² PRO-HOOD. Single layer lens. Used with the ASSLB, FBBRACKET, or BRACKET bracket | | | | | |
| 2000V | Replacement lens, with hook & pile attachment, for OLDER DESIGN 8cal/cm² to 20cal/cm² PRO-HOOD. Single layer lens. Used with the ASSLB, FBBRACKET, or BRACKET brack | | | | | |
| 4000V | NEW CLEARER LENS Replacement lens, with hook & pile attachment, for 31 cal/cm ² to 55 cal/cm ² PRO-HOOD. Dual layer lens. Used with the ASSLB, FBBRACKET, or BRACKET brackets. | | | | | |
| 4000VB | NEW CLEARER LENS Replacement lens, with hook & pile attachment, for 31 cal/cm ² to 55 cal/cm ² PRO-HOOD. Dual layer lens (clear and tinted). Indudes BRACKET for front brim hard hat. | | | | | |
| 4000VFB | NEW CLEARER LENS Replacement lens, with hook & pile attachment, for 31 cal/cm ² to 55 cal/cm ² PRO-HOOD. Dual layer lens (clear and tinted). Indudes FBBRACKET for full brim hard hat. | | | | | |
| 10000V | Replacement lens, with hook & pile attachment, for 75 cal/cm ² to 100 cal/cm ² PRO-HOOD. Dual layer lens (clear and tinted). Used with the ASSLB, FBBRACKET, or BRACKET brackets. | | | | | |

SALISBURY by Honeywell 101 E. Crossroads Pkwy., Ste. A Bolingbrook, IL 60440 • U.S.A. Toll Free: 877.406.4501 • U.S.A. Toll Free Fax: 866.824.4922

REPLACEMENT BRACKETS, PROTECTIVE NETS & SAFETY GLASSES

REPLACEMENT BRACKETS

| Cat. No. | Description | | | | |
|-----------|---|--|--|--|--|
| ASCP | Replacement chin cup for AS1000 series shields. | | | | |
| BRACKET | Universal dielectric hard hat bracket. Used with front brim hard hats. | | | | |
| FBBRACKET | Universal dielectric hard hat bracket. Used with full brim hard hats. | | | | |
| ASSLB | Dielectric bracket, fits slotted front brim hard hats. Used with all AS1000 Series lenses. | | | | |
| ASRHG4 | Ratcheted head gear with 4″ arc guard. Used with AS1000FSR lens. | | | | |



ASRHG4

SALISBURY'S FIRE RESISTANT HAIRNET AND BEARDNET

give added protection in any industry that requires the worker to wear a hairnet or beardnet. The hairnet and beardnet have an ATPV rating of 2.4 cal/cm² and are available in gray and made of a washable 1.7 oz/yd² (58 g/m2) Woven Nomex® fabric. Meets current ASTM F1506 standards.

| Cat. No. | Description | | |
|----------|--|--|--|
| HN-1 | FR protective hairnet, 2.4 cal/cm² 1.7 oz/yd² (58 g/m²) woven Nomex® | | |
| BN-1 | FR protective beardnet, 2.4 cal/cm² 1.7 oz/yd² (58 g/m²) woven Nomex® | | |

SAFETY GLASSES > are anti-fogging, anti-scratch and anti-static with 99.9% UV protection. These glasses meet current ANSI Z87.1, 2003 and CSA Z94.3* standards.

*The CSA Z94.3 standard applies to eye and face protectors used in all occupational and educational operations or processes involving hazards to the eyes or face.

| Cat. No. | Description |
|-------------|------------------------|
| TS56505GRY | Clear lens, gray frame |
| TS56505GRYA | Amber lens, gray frame |
| TS56505GRYS | Smoke lens, gray frame |





BN-1





ARC FLASH PROTECTION HOODS - AFHOODS

10 - 28 CAL/CM²



AFHOOD15

14



◄ SALISBURY'S ARC FLASH HOODS (balaclava) create 360 degree head and neck protection from arc flash dangers, when used with a AS1000 Series Faceshield/Hard Hat/Chin Cup Unit. Each Arc Flash Hood is made from two layers of rib knit material and has an elastic face opening that maintains its shape and size.

The AFHOOD10 has an ATPV rating of 10 cal/cm². The AFHOOD15 has an ATPV rating of 15 cal/cm². The AFHOOD20 has an ATPV rating of 20 cal/cm². Both the AFHOOD28FF and the AFHOOD28EO have an ATPV rating of 28 cal/cm². All are made from FR materials.

CAUTION: Arc Flash Hoods must be worn in combination with a faceshield in order to comply with the requirements of NFPA 70E and will protect 360° inside the arc flash boundary.

| Cat. No. Description | |
|----------------------|-----------------------------------|
| AFHOOD10 | 10 cal/cm ² protection |
| AFHOOD15 | 15 cal/cm ² protection |
| AFHOOD20 | 20 cal/cm ² protection |
| AFHOOD28FF | 28 cal/cm ² protection |
| AFHOOD28EO | 28 cal/cm² protection, 2-eye hood |



AFHOOD28E0



ARC FLASH PROTECTION AS1000HAT & AFHOOD KIT

► THE AS1000HAT & AS1200HAT KITS make your Personal Protective Equipment purchasing even easier. These convenient kits contain an AS1000HAT or AS1200HAT, a 10 cal/cm², 15 cal/cm², or 20 cal/cm² ATPV rated AFH00D, safety glasses and an ASBAG.

The AS1000HAT has an ATPV rating of 10 cal/cm². The lens provides a 7.5" x 20" viewing area with an extra light tint. The AS1200HAT has an ATPV rating of 12 cal/cm².

The SKA kits are an ideal kit to use with PPE programs that exceed 8 cal/cm² or with 8 cal/cm² to 12 cal/cm² ATPV rated coveralls and jackets.

NOTE: Due to AS1000HAT ATPV rating of 10 cal/cm², protection greater than 10 cal/cm² cannot be achieved. Due to AS1200HAT ATPV rating of 12 cal/cm², protection greater than 12 cal/cm² cannot be achieved.

| Cat. No. | Description | | | | | |
|------------|---|--|--|--|--|--|
| SKA10 | ATPV 10 cal/cm ² Kit 10 cal/cm ² AFHOOD with 10 cal/cm ² AS1000HAT, ANSI rated safety glasses and ASBAG. | | | | | |
| SKA10-1200 | ATPV 10 cal/cm ² Kit 10 cal/cm ² AFHOOD with 12 cal/cm ² AS1200HAT, ANSI rated safety glasses and ASBAG. | | | | | |
| SKA15 | ATPY 10 cal/cm ² Kit 15 cal/cm ² AFHOOD with 10 cal/cm ² AS1000HAT, ANSI rated safety glasses and ASBAG. | | | | | |
| SKA15-1200 | ATPV 12 cal/cm ² Kit 15 cal/cm ² AFHOOD with 12 cal/cm ² AS1200HAT, ANSI rated safety glasses and ASBAG. | | | | | |
| SKA20 | ATPV 10 cal/cm ² Kit 20 cal/cm ² AFHOOD with 10 cal/cm ² AS1000HAT, ANSI rated safety glasses and ASBAG. | | | | | |
| SKA20-1200 | ATPV 12 cal/cm ² Kit 20 cal/cm ² AFHOOD with 12 cal/cm ² AS1200HAT, ANSI rated safety glasses and ASBAG. | | | | | |









SKA10

IMPORTANT: THE MAXIMUM ARC FLASH PROTECTION OF A KIT IS EQUAL TO THE LOWEST CAL/CM² RATING OF ANY COMPONENT IN THE SELECTED SAFETY KIT.

COMPACT PRO-AIR™ ACAIR2000®

ARC FLASH PROTECTION HOOD COMPACT POWERED AIR SYSTEM





Use this unit with Salisbury Arc Flash Protective PRO-HOODs.

◄ SALISBURY'S PRO-AIR ACAIR2000 - NEW UPGRADED CIRCUIT BOARD

AND BATTERY Salisbury's PRO-AIR ACAIR2000 system is designed to blow forced ambient air through a single intake hose, providing fresh oxygen to the worker and reducing the hazardous effects of shield fogging. The unit is microprocessor controlled and operates automatically by blowing air continuously for over three hours on one charge. On the back of the unit is a button that pauses the continuous flow, if needed. Use this unit with Salisbury's PRO-HOOD® and PRO-WEAR® arc flash protection clothing.

The PRO-AIR ACAIR2000 compact powered air system easily mounts to most standard hardhats and functions in one lightweight (less than 10 oz.) easy to use unit. The unit cools the worker and reduces fatigue while wearing a Salisbury Arc Flash PRO-HOOD.

The PRO-AIR ACAIR2000 includes a lightweight blower assembly, universal band, bendable intake hose, Ni-MH rechargeable batteries, and an AC wall charger.

| Cat. No. | Description |
|----------|-------------|
| | |

| CAIR2000 IMPROVED | PRO-AIR | Lightweight | air sy | ystem f | or PR | O-HOODs |
|-------------------|---------|-------------|--------|---------|-------|---------|
|-------------------|---------|-------------|--------|---------|-------|---------|

AIR FLOW HOOD SYSTEM & COMPACT PRO-AIR™ ACAIR102

ARC FLASH PROTECTION HOOD COMPACT POWERED AIR SYSTEMS



► NEW SALISBURY PRO-AIRTM AIR FLOW HOOD SYSTEM Salisbury's NEW PRO-AIR, Air Flow Hood System is integrated with Salisbury's PRO-HOOD® Arc Flash Protection Hood. Now, all Salisbury PRO-HOOD Arc Flash Protection Hoods are available with an optional integrated cooling system. This newest addition to the PRO-AIR line of products provides additional air flow and cools the worker. This unit is excellent in warm conditions or confined spaces. The easy to wear system is lightweight, compact, and easy to use. The system is designed to provide the worker with approximately 80cfm of air flow throughout the breathing zone. The unit is powered by 8 AA batteries and is designed to maintain a useful continuous life of up to 35hrs at 80cfm. The unit is non-filtered and is not considered a respirator.

| Cat. No. | Description |
|------------|--|
| FH8BL-C | NEW 8 cal/cm² arc flash hood w/ air system |
| FH11BL-C | NEW 12 cal/cm² arc flash hood w/ air system |
| FH20BL-C | NEW 20 cal/cm² arc flash hood w/ air system |
| FH31RB-C | NEW 31 cal/cm² arc flash hood w/ air system |
| FH40GY-C | NEW 40 cal/cm² arc flash hood w/ air system |
| FH40GYLT-C | NEW 40 cal/cm² arc flash hood w/ air system |
| FH55GY-C | NEW 55 cal/cm² arc flash hood w/ air system |
| FH75GY-C | NEW 75 cal/cm² arc flash hood w/ air system |
| FH100TW-C | NEW 100 cal/cm² arc flash hood w/ air system |
| | |

► THE SALISBURY PRO-AIR[™] is a belt mounted COMPACT POWERED AIR SYSTEM that provides a continuous flow of filtered air to reduce worker fatigue and provide additional comfort when working in hot and humid conditions. The PRO-AIR integrates with the full ATPV range of Salisbury's PRO-HOOD® line and easily attaches inside the hood using the exclusive Salisbury hook and pile looped fastener system.

The PRO-AIR kit consists of a blower unit, belt and comfort pad, rechargeable battery pack, breathing hose and battery charger. Blower unit and hose are covered with a fire resistant material to meet NFPA 70E requirements. The PRO-AIR kit is shipped in a durable carrying case.

NOT NIOSH APPROVED.

| Cat. No. | Description |
|----------|---|
| ACAIR102 | PRO-AIR Compact Powered Air System, Complete Kit |
| AC102 | Blower unit, battery, belt, back support, and fire resistant mesh bag |
| AC103 | PRO-AIR battery |
| A168091 | Replacement air filter cartridges |
| AC124 | O-Rings for air filters |
| AC129 | Y- shaped breathing hose |
| AC129FR | Fire retardent tube covers for AC129 (3) |
| AC131 | Single unit battery charger |
| AC135 | Compact Powered Air System carrying case |



Back View

Back View - open mesh bag

NOTE: Units provided with standard U.S. two prong blade electrical plugs. The plugs are for use in North and Central America and Japan. For all other requirements, please contact Salisbury International Customer Service.